



HYDROLAB HL4 Sonde, Internal Battery Power, Temperature, Other Integrated Sensors

Product #: HL4TABATT

USD Price: Contact Hach

The HYDROLAB HL4 is perfectly suited for spot monitoring or continuous deployments in a wide range of freshwater applications. Lightweight, portable and flexible, this multi-parameter sonde helps you quickly monitor watershed conditions. The field proven sensor options coupled with the robust construction and easy calibration delivers high quality reliable data. The HL4 sonde has a temperature sensor, four sensor ports and an optional internal depth sensor. The software allows for easy data retrieval and setup of logging files.

Ease of portability between sites and installation

The sonde's lightweight and compact design readily accesses difficult locations and fits inside protective housing -2" wells. Its durable design provides long term usage for a variety of applications.

Perfect for spot monitoring and short-term monitoring studies

Includes an internal memory of 4GB for logging data plus an optional internal battery pack, and flexible for many applications.

Easy to use instrument management and control software

Has guided calibration tasks and instructions, plus real time measurements in graphical and tabular formats.

Specifications

Battery Life:	75 days
Communication:	Communications module: USB, SDI-12, RS232 Modbus, RS485 Modbus and RS232 TTY
Dimensions:	Length: 24.5 in (62.23 cm) with internal battery pack and standard sensor guard
Measuring Range Depth:	656 ft (200 m) minimum
Memory:	4GB
Number of Analog Ports:	4
Operating Temperature Range:	23 - +122 °F , non-freezing
Power Supply:	6 - 24 VDC (12 VDC nominal) applied to the communications module, 12 VDC: 250 mW average, 18 W peak
Sample Rate:	1 Hz minimum (once per second)
Sensor Ports:	6 sensor ports available 2 fixed sensor ports for temperature and optional depth sensor only 4 ports for integrating other sensor options Parameters available depends on sensor installed Maximum of 2 ports available for optical dissolved oxygen and another optical sensor
Standard storage temperature:	34 - +122 °F (1 - +50 °C)

Weight:

5 lb (2.2 kg)