



Lufft WS700 Smart Weather Sensor

Product #: 8380.1
USD Price: Contact Hach

The WS700-UMB is an all-in-one weather sensor with measurement of temperature, relative humidity, precipitation intensity, precipitation type, precipitation quantity, air pressure, wind direction, wind speed and radiation. It is part of the WS product family of professional intelligent measuring sensors with a digital interface and an integrated design with ventilated radiation protection for various environmental applications. One external temperature sensor is connectable.

All-in-one housing concept & easy installation

All-in-one housing concept of a compact weather sensor combining several measurement parameters in one housing with only a single cable connection.

Maintenance-free operation

Maintenance free operation as there are no moving parts that can wear out. Precipitation is measured with a radar sensor.

Flexible interfaces and telegrams

SDI-12 and RS485 with supported protocols UMB-Binary, UMB-ASCII, Modbus-RTU, Modbus-ASCII, and XDR.

Aspirated radiation shield

Specifications

*Parameters Measured:	Air Temperature
	Relative Humidity
	Precipitation Intensity
	Precipitation Type
	Precipitation Quantity
	Air Pressure
	Wind Direction
	Wind Speed
	Solar Radiation
Air Pressure:	Accuracy: ± 0.5 hPa (0 - +104 °F) or ± 0.5 hPa (0 - +40 °C)
	Measuring range: 300 - 1200 hPa
	Measurement technology: MEMS capacitive

Air Temperature:	Accuracy: ± 0.4 °F (-4 - +122 °F) or ± 0.2 °C (-20 - +50 °C), otherwise ± 0.9 °F (# -22 °F) or ± 0.5 °C (# -30 °C)
	Measuring range: -58 - +140 °F (-50 - +60 °C)
	Measurement technology: NTC
	Resolution: 0.1 °C (-20 - +50 °C), otherwise 0.2 °C
Analog Inputs:	1
Cable Connection:	Open wires
Cable Length:	33 ft (10 m)
Communication:	SDI-12 and RS485 with supported protocols
	UMB-Binary, UMB-ASCII, Modbus-RTU, Modbus-ASCII, XDR
Dimensions:	Ø150 x 344 mm
Interface:	RS485 2 wire
	Baud rate: 1200 - 38400 bit/s (Standard: 19200) or SDI-12
IP Rating:	IP66
Material Enclosures:	Plastics (PC)
Operating Humidity:	0 - 100 %
Operating Temperature Range:	-50 - +60 °C
Power Consumption:	40 VA
Power Supply:	12 - 24 VDC
Precipitation:	Accuracy: 20 %
	Measuring range: 0 - 200 mm/h
	Measurement technology: 24 GHz Radar
Relative Humidity:	Accuracy: ± 2 % RH
	Measuring range: 0 - 100 % RH
	Measurement technology: Capacitive
Solar Radiation:	Accuracy: 5 %
	Measuring range: Maximum operational irradiance; 1400 W/m ²
	Measurement technology: Si-photodiode, optoelectric
	Non-linearity: N.A.
	Non-stability: N.A.
Water Level:	Accuracy: ± 0.3 m/s or ± 3 % (0 - 35 m/s) ± 5 % (#35 m/s) RMS
	Measuring range: 0 - 75 m/s
	Measurement technology: Ultrasonic
Weight:	3.3 lb (# 1.5 kg)
Wind Direction:	Accuracy: # 3° RMSE # 1.0 m/s
	Measuring range: 0 - 359.9 °
	Measurement technology: Ultrasonic
Wind Speed:	Accuracy - $\pm 0,3$ m/s or ± 3 % (0 - 35 m/s) ± 5 % (#35 m/s) RMS

Measurement Range - 0 - 75 m/s

Measurement Technology - Ultrasonic