



Lufft Intelligent Road Sensor IRS31 Pro-UMB, 328 ft Supply Cable, 1 Temperature Depth Sensor

Product #: 8910.U101
USD Price: Contact Hach

The passive intelligent road sensor IRS31Pro-UMB is flush-mounted in the road. The two part housing design allows the combined sensor/electronics unit to be removed for maintenance or calibration at any time. The following variables are recorded: Road surface temperature, water film height up to 4 mm, freezing temperature for different de-icing materials (NaCl, MgCl, CaCl), road condition (dry/damp/wet/ice or snow, damp with salt, wet with salt), friction (Grip), ice percentage. Optional: 2 additional depth temperatures, e.g. at 5 cm and 30 cm. The measurement data are available for further processing in the form of a standard protocol (Lufft UMB protocol).

Invasive precise point measurement of the road condition

Invasive sensors embedded in the road allows all time measurements of water film height, road surface and depth temperature and road condition even at heavy traffic conditions.

Maintenance, calibration and replaceability

Sensor consists of two parts: replaceable sensor head with electronics and fixed mounted socket.

Power consumption

Low energy consumption allows solar operation.

Invasive technology allows

Permanent usage on runways where non-invasive sensors cannot be used.

Specifications

*Parameters Measured:	Road surface temperature
	Water film (Height up to 4 mm)
	Freezing temperature (for different de-icing materials (NaCl, MgCl, CaCl))
	Road condition (dry/damp/wet/ice or snow/moist with salt/wet with salt)
	Friction
	Ice Percentage
	Depth (2 additional depth sensors)
Accuracy:	Road surface temperature: ± 0.2 °F (-4 - +68 °F), else ± 0.4 °F
	Freezing point: ± 1 °F (32 - +27.5 °F), else ± 20 % of average value (at de-icing agent NaCl)
	Water film height: 0.2 mm - 3 mm: better than ± 30 %
Cable Connection:	Open wires 0.5 mm ²

Cable Length:	328 ft (100 m)
Communication:	SDI-12, RS485-UMB
Connector (text):	Cable 0.5 mm ²
Cooling Sensor:	N.A.
Detectable road conditions:	Dry/moist/wet/moist with salt/wet with salt/ice
Dimensions:	Ø 4.72441 in, H 1.97 in (Ø 120 mm, H 50 mm)
Height above Absolute Altitude:	9843 ft (3000 m)
Interface:	RS485
	Baud rate: 2400 - 38400 bit/s (Standard: 19200) or SDI-12
IP Rating:	IP68
Material Enclosures:	Salt , UV resistant modified PTFE
Measurement distance:	in-situ
Measurement technology:	Ice percentage: Conductivity measurement
	Water film: Radar measurement
	Road surface temperature: NTC
Measuring Range:	Road surface temperature: -40 - +176 °F
	Freezing point: -40 - +32 °F
	Water film height: 0 - 0.16 in
	Friction (Grip) [slippery-dry]: 0 - 1
	Ice Percentage: 0 - 100 %
Number of Depth Sensors:	1
Number of Depth Temperature Sensors:	1
Number of Related Temperature Sensors:	1
Operating Humidity:	0 - 100 % RH
Operating Temperature Range:	-40 - +176 °F
Parameters Measured:	Road surface temperature
	Water film: Height up to 4 mm
	Freezing temperature: for different de-icing materials (NaCl, MgCl, CaCl)
	Road condition: dry/damp/wet/ice or snow/moist with salt/wet with salt
	Friction
	Ice Percentage
	Depth: 2 additional depth sensors
Power Supply:	9 - 14 VDC, nominal 12 V
Product highlights:	Two part housing design allows easy maintenance/re-calibration
	Low energy consumption allows solar operation
	Radar principle to measure water film
Resolution:	Road surface temperature: 32.18 °F (0.1 °C)
	Freezing point: 32.18 °F (0.1 °C)

	Water film height: 0.0004 in (0.01 mm)
Road dampness:	Unit: dry/damp/wet/damp with salt/wet with salt
Slippery road conditions:	Unit: no ice/snow, snow, ice
Standard storage temperature:	-40 - +158 °F (in packaging)
Weight:	Approx. 1.8 lb (800 g) without cable and without external temperature probe