



SUNA Submersible Underwater Nutrient Analyzer, Seawater, 1688 cm³, RS232, Analog, SDI12, USB

Product #: USD Price: SUNA.10102S

\$34,690.00

Industry-leading sensor for nitrate measurement

The SUNA V2 UV nitrate sensor is the ultimate solution for real-time nutrient monitoring. This sensor measures nitrate over a wide range of environmental conditions, from blue-ocean nitraclines to storm runoff in rivers and streams.

Full UV spectrum range for maximum accuracy

Real-time nitrate calculation

SUNA V2 (2k) option for floats, gliders, and other AUVs Depth rating of 2000 m for deep ocean applications

SUNA V2 (2k) option for floats, gliders, and other AUVs Depth rating of 2000 m for deep ocean applications

Specifications

Accuracy:	4 μΜ
Anti-fouling:	No
Calibration type:	Seawater
Current Draw:	625 mA @ 12 V
Data Storage:	N/A
Depth Rating:	1640.42 ft (500 m)
Displacement:	1688 cm ³
Input Voltage:	8 – 18 VDC
Kit Option:	Yes
Lamp Lifetime:	900 hr
Lamp Type:	Deuterium
Path Length:	0.197 in (5 mm)
Precision:	0.3 μM
Storage and Communication Options:	USB
Telemetry Selections:	RS-232, analog (0-5 VDC), SDI-12

Wavelength Range:190–370 nmWeight in air, water:8.6 lbs (3.9 kg)